

Ensurepass.com Easy Test! Easy Pass!



Vendor: Cisco

Exam Code: 642-737

**Exam Name: Implementing Advanced Cisco Unified
Wireless Security (IAUWS) v2.0**

Version: DEMO

QUESTION 1

Which statement describes the major difference between PEAP and EAP-FAST client authentication?

- A. EAP-FAST requires a backend AAA server, and PEAP does not.
- B. EAP-FAST is a Cisco-only proprietary protocol, whereas PEAP is an industry-standard protocol.
- C. PEAP requires a server-side certificate, while EAP-FAST does not require certificates.
- D. PEAP authentication protocol requires a client certificate, and EAP-FAST requires a secure password.

Answer: C

QUESTION 2

Refer to the exhibit. What is the 1.1.1.1 IP address?



- A. the controller virtual interface IP address
- B. the controller management IP address
- C. the controller AP-manager IP address
- D. the RADIUS server IP address
- E. the lightweight AP IP address
- F. the wireless client IP address

Answer: A

QUESTION 3

What are the four packet types that are used by EAP? (Choose four.)

- A. EAP Type
- B. EAP Request
- C. EAP Identity
- D. EAP Response
- E. EAP Success
- F. EAP Failure
- G. EAP Authentication

Answer: BDEF

QUESTION 4

When a supplicant and AAA server are configured to use PEAP, which mechanism is used by the client to authenticate the AAA server in Phase One?

- A. PMK
- B. shared secret keys
- C. digital certificate
- D. PAC

Answer: C

QUESTION 5

Which EAP types are supported by MAC 10.7 for authentication to a Cisco Unified Wireless Network?

- A. LEAP and EAP-Fast only
- B. EAP-TLS and PEAP only
- C. LEAP, EAP-TLS, and PEAP only
- D. LEAP, EAP-FAST, EAP-TLS, and PEAP

Answer: D

QUESTION 6

What are two of the benefits that the Cisco AnyConnect v3.0 provides to the administrator for client WLAN security configuration? (Choose two.)

- A. Provides a reporting mechanism for rogue APs
- B. Prevents a user from adding any WLANs
- C. Hides the complexity of 802.1X and EAP configuration
- D. Supports centralized or distributed client architectures
- E. Provides concurrent wired and wireless connectivity
- F. Allows users to modify but not delete admin-created profiles

Answer: CD

QUESTION 7

When using the Standalone Profile Editor in the Cisco AnyConnect v3.0 to create a new NAM profile, which two statements describe the profile becoming active? (Choose two.)

- A. selects the new profile from NAM
- B. selects "Network Repair" from NAM
- C. becomes active after a save of the profile name
- D. ensures use of "configuration.xml" as the profile name
- E. ensures use of "config.xml" as the profile name
- F. ensures use of "nam.xml" as the profile name

Answer: BD

QUESTION 8

Which two parameters can directly affect client roaming decisions? (Choose two.)

- A. SNR
- B. RSSI
- C. MFP status
- D. RF fingerprinting
- E. RRM

Answer: AB

QUESTION 9

Which three parameters can be communicated between a Cisco WLC v7.0 and Cisco Compatible Extensions v4-enabled client to improve a secure roaming connection? (Choose three.)

- A. minimum SNR
- B. transition time
- C. scan threshold
- D. hysteresis
- E. PER
- F. MIC errors

Answer: BCD

QUESTION 10

Which three Cisco WLC v7.0 CLI family of commands would be appropriate to troubleshoot a wireless client failure for connection to an AP? (Choose three.)

- A. debug capwap
- B. debug mac addr
- C. debug ccxdiag
- D. debug dhcp
- E. debug ap
- F. debug dtls
- G. debug aaa

Answer: BDG

QUESTION 11

What is the best method to verify AP parameters that are seen from a wireless client?

- A. WCS debug commands
- B. ACS log files
- C. WCS show commands
- D. AP debug commands
- E. packet analyzers

Answer: E

QUESTION 12

Drag and Drop Question

Click and drag the wired-side tracing method on the left to its correct description on the right in a Cisco Unified Wireless Network solution based on version 7.0

Click and drag the wired-side tracing method on the left to its correct description on the right in a Cisco Unified Wireless Network solution based on version 7.0.

switch port tracing	Detector AP uses wired-side ARPs
adaptive wIPS	Detector AP connects as client to rogue AP
H-REAP	Supported on Cisco WCS and uses CDP
RLDP	
autocontainment	
rogue detector	

Answer:

rogue detector
RLDP
switch port tracing

Ensurepass.com Members Features:

1. Verified Answers researched by industry experts.
2. Q&As are downloadable in PDF and VCE format.
3. 98% success Guarantee and **Money Back** Guarantee.
4. Free updates for **180** Days.

View list of All Exam provided:

<http://www.ensurepass.com/certifications?index=A>

To purchase Lifetime Full Access Membership click here:

<http://www.ensurepass.com/user/register>

Valid Discount Code for 2014: SFOH-FZA0-7Q2S

To purchase the HOT Exams:

<u>Cisco</u>		<u>CompTIA</u>		<u>Oracle</u>	<u>VMWare</u>	<u>IBM</u>
<u>100-101</u>	<u>640-554</u>	<u>220-801</u>	<u>LX0-101</u>	<u>1Z0-051</u>	<u>VCAD510</u>	<u>C2170-011</u>
<u>200-120</u>	<u>640-802</u>	<u>220-802</u>	<u>N10-005</u>	<u>1Z0-052</u>	<u>VCP510</u>	<u>C2180-319</u>
<u>300-206</u>	<u>640-816</u>	<u>BR0-002</u>	<u>SG0-001</u>	<u>1Z0-053</u>	<u>VCP550</u>	<u>C4030-670</u>
<u>300-207</u>	<u>640-822</u>	<u>CAS-001</u>	<u>SG1-001</u>	<u>1Z0-060</u>	<u>VCAC510</u>	<u>C4040-221</u>
<u>300-208</u>	<u>640-864</u>	<u>CLO-001</u>	<u>SK0-002</u>	<u>1Z0-474</u>	<u>VCP5-DCV</u>	<u>RedHat</u>
<u>350-018</u>	<u>642-467</u>	<u>ISS-001</u>	<u>SK0-003</u>	<u>1Z0-482</u>	<u>VCP510PSE</u>	<u>EX200</u>
<u>352-001</u>	<u>642-813</u>	<u>JK0-010</u>	<u>SY0-101</u>	<u>1Z0-485</u>		<u>EX300</u>
<u>400-101</u>	<u>642-902</u>	<u>JK0-801</u>	<u>SY0-301</u>	<u>1Z0-580</u>		
<u>640-461</u>	<u>700-302</u>			<u>1Z0-820</u>		

