



Vendor: Cisco

Exam Code: 642-999

Exam Name: Implementing Cisco Data Center Unified Computing (DCUCI)

Version: Demo

QUESTION 1

When upgrading a standalone Cisco UCS C-Series server, which method is correct?

- A. direct upgrade on all components
- B. Cisco Hardware Upgrade Utility
- C. Cisco Host Upgrade Utility
- D. Cisco Server Upgrade Utility

Correct Answer: C

QUESTION 2

In a standalone Cisco UCS C-Series server, which recommendations can be used to upgrade the BIOS?

- A. Cisco IMC
- B. Cisco UCS Manager
- C. iFlash32 Utility
- D. Flash ROM Utility
- E. EFI Interface
- F. Cisco Host Upgrade Utility
- G. USB Flash Utility

Correct Answer: F

QUESTION 3

What are the default settings of the Cisco IMCCIMC NIC properties on a standalone Cisco UCS C-Series server?

- A. 'Shared LOM' NIC mode with 'Active-active' NIC redundancy and DHCP enabled
- B. 'Shared LOM' NIC mode with 'Active-standby' NIC redundancy and DHCP enabled
- C. 'Dedicated' NIC mode with 'Active-standby' NIC redundancy DHCP disabled
- D. 'Dedicated' NIC mode with 'None' NIC redundancy and DHCP enabled
- E. 'Cisco Card' NIC mode with 'Active-active' NIC redundancy and DHCP enabled

Correct Answer: D

QUESTION 4

Which ports can access the Cisco IMC if you select Shared LOM NIC mode in the Cisco IMC Configuration Utility for a Cisco UCS C-Series server?

- A. the ports on an installed Cisco network adapter card

- B. the two 1-Gb Ethernet ports
- C. the two 10/100 management ports
- D. the two 10/100 management ports, but each port has a default setting

Correct Answer: B

QUESTION 5

Which NIC redundancy modes allow the LOMs to be discovered by the operating system or hypervisor?

- A. Dedicated mode
- B. Active/Active
- C. Active/Standby
- D. Cisco Card Mode

Correct Answer: A

QUESTION 6

Which two are true with respect to the unified ports on the Cisco Unified Computing System 62XX Fabric Interconnect? (Choose two.)

- A. The port mode is automatically discovered after plugging in a LAN or Fibre Channel-attached cable.
- B. By default, unified ports that are changed to Ethernet port mode are set to uplink Ethernet port type.
- C. Ethernet ports must be grouped together in a block and must start with the first port and end with an odd numbered port.
- D. Alternating Ethernet and Fibre Channel ports is supported on the expansion module.
- E. After making port mode changes on an expansion module, the module will reboot.
- F. In a standalone configuration, making port mode changes to the fixed module will not cause the fabric interconnect to reboot.

Correct Answer: CE

QUESTION 7

Which two are true with respect to the switching modes on the Cisco Unified Computing System 62XX Fabric Interconnect? (Choose two.)

- A. End-host mode presents a link to a northbound uplink switch as a host trunk with loop detection that is provided by STP.
- B. For northbound traffic, server MAC addresses are statically pinned to an uplink; the return

- path is controlled by the unified fabric switches.
- C. A fabric interconnect port in Ethernet switching mode appears to the uplink switch as a host with many MAC addresses.
 - D. Server-to-server traffic on a common VLAN are locally switched by the fabric interconnect and not the northbound switches.
 - E. A MAC forwarding table is not used to forward traffic to the uplink switch.
 - F. A MAC address forwarding table is maintained for server-to-server communications across VLANs.

Correct Answer: DE

QUESTION 8

What is true statement concerning port personalities on the Cisco Unified Computing System 62XX Fabric Interconnect?

- A. Fibre Channel uplink ports must operate in Fibre Channel switching mode.
- B. The fabric interconnects use native FCoE storage ports to directly attach to the SAN infrastructure.
- C. By default, all Fibre Channel ports are unconfigured.
- D. The Fibre Channel uplink ports do not support VSAN trunking and Fibre Channel port channels.
- E. The Fibre Channel storage ports support VSAN trunking and Fibre Channel port channels.

Correct Answer: C

QUESTION 9

What is a true statement concerning automatic Fibre Channel pinning on a Cisco Unified Computing System 62XX Fabric Interconnect?

- A. By default, uplink Fibre Channel interfaces are configured for VSAN trunking.
- B. Using NPV, each downstream server will be pinned to an uplink port that is based on a PIN group.
- C. The Fibre Channel pinning process is implemented differently than end-host MAC address pinning.
- D. With VSAN trunking, the automatic pinning of server traffic to Fibre Channel uplink ports will be based on the server WWN.

Correct Answer: D

EnsurePass.com Members Features:

1. Verified Answers researched by industry experts.
2. Q&As are downloadable in PDF and VCE format.
3. 98% success Guarantee and **Money Back** Guarantee.
4. Free updates for **180** Days.
5. **Instant Access to download the Items**

View list of All Exam provided:

<http://www.ensurepass.com/certifications?index=A>

To purchase Lifetime Full Access Membership click here:

<http://www.ensurepass.com/user/register>

Valid Discount Code for 2015: JREH-G1A8-XHC6

To purchase the HOT Exams:

<u>Cisco</u>		<u>CompTIA</u>		<u>Oracle</u>	<u>VMWare</u>	<u>IBM</u>
100-101	640-554	220-801	LX0-101	1Z0-051	VCAD510	C2170-011
200-120	200-101	220-802	N10-005	1Z0-052	VCP510	C2180-319
300-206	640-911	BR0-002	SG0-001	1Z0-053	VCP550	C4030-670
300-207	640-916	CAS-001	SG1-001	1Z0-060	VCAC510	C4040-221
300-208	640-864	CLO-001	SK0-003	1Z0-474	VCP5-DCV	RedHat
350-018	642-467	ISS-001	SY0-301	1Z0-482	VCP510PSE	EX200
352-001	642-813	JK0-010	SY0-401	1Z0-485		EX300
400-101	642-832	JK0-801	PK0-003	1Z0-580		
640-461	642-902			1Z0-820		



Guaranteed Success with EnsurePass VCE Software & PDF File